

DynamicChairDisplay

Motorised monitor with manual rotation







FEATURES

- Adapts to multiple armrests
- Motorised adjustable angle
- Maintenance free

- HDCP compliant
- Safety system
- Serial control & Remote diagnose

GENERAL

DynamicChairDisplays have been designed for integration into chairs' armrests.

DynamicChairDisplay is a retractable motorised monitor to be integrated in chair's armrests. The monitor is only visible when in use and it is safely stored in the armrest when not needed.

This elegant aluminium screen has an automatic vertical extraction movement with manual rotation towards the user, followed by a motorised tilt adjustment.

The monitor housing is made of milled aluminium with anodised nish. Its mechanism is robust and silent and the whole solution is integrated in a compact block, being very easy to install. DynamicChairDisplay is available in 15,6".

TECHNICAL SPECIFICATIONS

| Display | |
|---------------------------------|--|
| Size | FULL HD 15.6" TFT Active Matrix, widescreen |
| Resolution | 1920 (h) x 1080 (v) |
| Brightness | 300 cd/m2 |
| Contrast ratio | 800:1 |
| Pixel | 0.1792 (h) x 0.1792 (v) mm |
| Viewing angle | 65°/80° (u/d) / 80°/80° (l/r) |
| Viewing area | 344.16 (h) x 193.59 (v) mm |
| LED backlight lifespan | 50.000 hrs |
| Response time | Tr + Tf 30 ms |
| Temperature (operating/storage) | Operating 0°C - +40°C Storage -20°C - +60°C |
| Materials | |
| Cabinet | Solid aluminium monitor housing in natural anodised finishing |
| Connectivity | |
| Input signal | DVI-I (1 input) – HDCP Compliant DVI-D (1 input) – HDCP Compliant |
| RJ45 CAT5 (with loop) | Addressable RS422 monitor control by AHnet protocol |
| | |

Up/Down control

| Control | |
|-------------------------------------|--|
| RJ45, RS-422 (I/O) | |
| Addressing | |
| Termination switch | |
| GPI | |
| Movement's Control | |
| User interface on monitor | (Up/Down) |
| Remote | RS-422 I/O/GPI |
| Electrical | |
| Low voltage (external power supply) | 100-240Vac, 47/63Hz, 12Vdc |
| Power consumption | 50W |
| Mechanical | |
| Monitor Dimensions: | |
| Screen | 583 x 462 x 97 mm [22.95"x18.18"x3.81"] |
| Weight | 16 kg / 35.2 lbs |
| Shipping Dimensions: | |
| Weight | 17 kg / 37.4 lbs |
| Shipping Box | 740 x 610 x 175 mm |

OPTIONS

GPI (SubD9)

- Touch screen
- USB integrated on cover plate
- 2 USB integrated on cover plate
- USB power integrated on cover plate
- Customised cover plate with speaker, voting system, USB connector
- Prepared for underneath installation, cover plate prepared to be veneered
- Additional customised laser engraved logotype on the cover plate
- Monitor housing anodised in different colours

CERTIFICATIONS

CE

WARRANTY

• 2 years general warranty

CONNECTIVITY PANEL



CONNECTIVITY

- 1- AHnet control interface
- 2- Power input
- 3- DVI-D video input digital
- 4- DVI-I video input analog/ digital

ARCHITECT'S SPECIFICATIONS

Low voltage professional electrically retractable 15,6" monitor for chair's armrests integration. Solid block of aluminium monitor housing in natural anodised finishing. Motorised lifting and angle adjustment with a single electrical engine for enhanced reliability. Manual horizontal adjustment (rotation towards the user) for improved user's safety.

DVI-I and DVI-D connectors. HDCP compliant inputs. Compatible with AHnet open protocol over RS-422, allowing independent remote control of up to 30 units over a daisy-chain CAT-5 or CAT-6 line. Additional control by means of the buttons integrated on the cover plate and on the monitor's housing that can be activated or deactivated by using the AHnet.

