

Drop

Display for wall integration





Brushed stainless steel



Aluminium



AH AKTHUR HOLM

FEATURES

- In- wall installation
- Brushed stainless steel/ Aluminium/ Glass front frame (depending on the model)
- Easy to install

- · Security anti-theft locking system
- Maintenance free
- HDCP compliant
- Energy saving design

GENERAL

Drop monitors have been designed for an easy in-wall installation. They are supplied with a separate box for fix mounting, while the screen itself provides a "clip-on front" system.

They are available with glass, brushed stainless steel and aluminium frames and provide options such as embedded PC, built-in camera and also with touch screen. All models are provided with a galvanised mounting box and are available in a variety of sizes, from 10" to 22".

TECHNICAL SPECIFICATIONS

AH22DI/ AH22DA/ AH22DG

Dis	n	la۷
013	y,	uy

Diopidy	
Size	Full HD 21.5" TFT Active Matrix, widescreen
Resolution	1920 (h) x 1080 (v)
Brightness	350 cd/m2
Contrast ratio	1000:1
Pixel	0.24975 (h) x 0.24975 (v) mm
Viewing angle	89°/89°(L/R) 89°/89°(U/D)
Viewing area	476.064 (h) x 267.786 (v) mm
LED backlight lifespan	50.000 hrs
Response time	Tr 12ms, Tf 10ms
Temperature (operating/storage)	Operating 0°C — +40°C Storage -20°C — +60°C
Materials	
Cabinet	Available with front in aluminium (A), stainless steel (I), or glass (G). With mounting box

Connectivity		
Input signal	DVI-I (1 input) - HDCP Compliant	
	DVI-D (1 input) - HDCP Compliant	
Electrical		
Loww voltage (external power supply)	100-240Vac, 50/60Hz, 12Vdc	
Power consumption	80W	
Mechanical		
Dimensions	547 x 339.3 x 73 mm	
	[21.54"x13.36"x2.87"]	
Weight	6 Kg / 13.2 lbs (Stainless Steel & Aluminium)	
	6.4 Kg / 14.1 lbs (Glass)	
Shipping Dimensions:		
Weight	7 Kg / 15.4 lbs (Stainless Steel & Aluminium)	
	7.4 Kg / 16.3 lbs (Glass)	
Shipping Box	650 x 470 x150 mm	

OPTIONS

- Touch screen
- Integrated industrial PC
- RS-232 remote control
- HD-BaseT for Video and Power over a single Cat5 cable


CERTIFICATIONS

CE

WARRANTY

• 2 years general warranty

CONNECTIVITY PANEL



CONNECTIVITY

- 1- Power input
- 2- DVI 2 video input
- 3- DVI 1/ DVI A video input

ARCHITECT'S SPECIFICATIONS

Professional 21.5" widescreen in-wall monitor. Frame available in aluminium, stainless steel or glass. DVI-I and DVI-D connectors. HDCP compliant inputs. Back box with hook system for easy installation. External power supply.

