


DynamicX2BarConnect

Aluminium retractable motorised monitor with connections bar



FEATURES

- Motorised monitor with integrated AV connectivity
- Automatic 20° inclination
- Interactive Setup Display
- Customisable cover plate
- Compact, space optimising and elegant solution
- HDCP compliant
- Energy saving design and Security system
- Easy installation
- Maintenance free and durable solution
- Serial control and remote diagnose
- AH-AMMC Auto Mechanical Movement Calibration
- Ideal for tables, desks and lecterns

GENERAL

DynamicX2 monitor is combined with BarConnect, a motorised, retractable connection system. This combination offers the best possible quality Full HD screen and personalised connectors options like HDMI, power USB, RJ45 USB and power outlets. The ergonomic angle of the bar enhances confort and usability. A safety mechanism stops the system in case of obstruction. The design is simple, with just 4 operation buttons. It is intuitive and easy to install. It offers cable management, improved table space and a neater environment.

DynamicX2 are elegant monitors built from a solid aluminium block and have a vertical motorised movement with automatic 20° inclination to ensure the best ergonomics, viewing angle

and visibility. This automatic tilting system provides a fast and silent response. It is a reliable, maintenance-free solution. DynamicX2 have slightly curved edges for a contemporary and longstanding look. The range is available from 15" to 22".

The anodised aluminium housing can be customised in different colours and finishes. The standard top-table cover plate is made of brushed stainless steel. It can optionally be supplied with a matt finish or it can disappear when the product is prepared for underneath installation.

DynamicX2 monitors are remotely controllable and diagnosable through the ERT interfaces in an easy and cost effective way.

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Bcelona, Spain · +34 938 502 376 · marketing@arthurholm.com
www.arthurholm.com

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

MONITOR - TECHNICAL SPECIFICATIONS

AH17DX2HDGA/BC

Display

Size	FULL HD 17.3" TFT Active Matrix
Resolution	1920 (h) x 1080 (v)
Brightness	400 cd/m2
Contrast ratio	600:1
Pixel	0.1989 (h) x 0.1989 (v) mm
Viewing angle	60°/80° (u/d) - 80°/80° (l/r)
Viewing area	381.888 (h) x 214.812 (v) mm
LED backlight lifespan	50.000 hrs
Response time	Tr 37 ms, Tf 3 ms
Temperature (operating/storage)	Operating 0°C – +40°C Storage -20°C – +60°C

Materials

Frame	Anodised Aluminium
Glass	AR 2-side with an anti-reflective coating on the glass surface. Thickness: 3.0 ± 0.3 mm
Cover plate	Stainless steel or matt

Connectivity

Input signal	DVI-I (1 input) Digital / Analogue DVI-D (1 input) Digital HDCP compliant
RJ45 CAT6 (with loop)	Addressable RS422 monitor control by AHnet protocol
GPI (SubD9)	Up/Down control

Control

RJ45, RS-422 (I/O)
Addressing
Termination switch
GPI
IR Remote control (monitor adjustments): 1 / 5

Movement's Control

User interface on monitor	(Up/Down)
Remote	RS-422 I/O/GPI

Electrical

Low voltage (external power supply)	100-240Vac, 47/63Hz, 12Vdc
Power consumption	50W

BARCONNECT - TECHNICAL SPECIFICATIONS

Connectivity

RJ45 CAT6 (with loop)	Addressable RS422 monitor control by AHnet protocol
Connectors	USB
	Power USB
	Power outlet
	RJ45
	HDMI

Engine

Control Up/Down	Buttons on cover plate, RS422 (RJ45 CAT6)
Electronic control	PWM

Electrical

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	10W

DYNAMICX2BARCONNECT - MECHANICAL

Monitor Dimensions

Screen	TBD
Upper Cover Plate	TBD
Housing below the table	TBD
Weight	TBD

Shipping Dimensions

Weight	TBD
Shipping Box	TBD

CERTIFICATIONS

- CE

WARRANTY

- 5 years limited warranty
- 2 years general warranty

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Bcelona, Spain · +34 938 502 376 · marketing@arthurholm.com
www.arthurholm.com

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.



Bottom connectivity for easy access and removal of monitor. Monitor housing total depth is 590 mm, plus additional spacing for connectors. Adjustable parameters through AHnet or ISD allowing calibration and adjustment of mechanics. Diagnostic readout on ISD for service and support.