


DB₂

HDCP compliant retractable motorised monitor









FEATURES

- Vertical motorised monitor with up to 20° inclination
- Adjustable screen angle tilt
- No cover plate required (monitor completey streamlined within the furniture)
- One operation sensor on top of the aluminium housing and one touch button on the glass (to rise and lower the screen and adjust the tilt angle)
- 20 mm maximum thickness
- Front double sided anti-reflective 2 sides coating 2 mm black edged glass

- · Can be veneered
- Interactive Setup Display (ISD)
- Maintenance free
- HDCP compliant
- Energy saving design, low consumption video controller
- Serial control and remote diagnosis
- Wireless connectivity for setup and control
- · Individual monitor addressing
- Auto Mechanical Movement Calibration (AH-AMMC)

GENERAL

Arthur Holm's DB2 is a motorised retractable monitor range that creates minimum impact on the furniture's design. It is easy to integrate, intuitive to use (one operation sensor located on the top of the monitor and one touch button on the glass) and almost invisible (no cover plate, neatly streamlined into furniture) when not operating. DB2 provides a harmonious silent drive with variable speeds. With a maximum thickness of 20 mm, this monitor range is elegant, beautiful from all angles and can be veneered for a seamless integration into furniture, creating a long lasting user's experience and delivering an exceptional images quality. We have selected the best possible aluminium finishing specifications in the world, providing the maximum technical and visual performance.

The screen is protected with an anti-reflective 2 side coating 2 mm black edged glass. DB2 are available from 10" to 23.8" with 2 DVI-HDCP compliant inputs and equipped with an Interactive Setup Display (ISD) allowing the control, setup and diagnose of the monitors. Monitors provide RS-422 I/O allowing the remote control of movements, speed, safety settings, brightness, contrast and backlight. The monitors are equipped with Auto Mechanical Movement Calibration (AH-AMMC). The use of the Arthur Holm's ERT will enable the address configuration of all the monitors installed in a table by simply pressing a button. The AHlink Android and iOS App allows getting the monitor's serial number without removing the unit from the table and allows access to the setup and control menu.

Display	
Size	FULL HD 17.3" TFT Active Matrix, widescreen format. LED backlight
Resolution	1920 (h) x 1080 (v)
Brightness	400 cd/m2
Contrast ratio	600:1
Pixel	0.1989 (h) x 0.1989 (v) mm
Viewing angle	60°/80°(u/d) 80°/80°(l/r)
Viewing area	381.888 (h) x 214.812 (v) mm
LED backlight lifespan	50,000 hrs
Response time	Tr 37ms, Tf 3 ms
Temperature (operating/storage)	Operating 0°C ~+40°C Storage -20°C ~+60°C
Materials	
Monitor housing	Solid mechanised aluminium housing with anodised finish. Front black serigraphed glass.
Connectivity	
Input signal	DVI-I (1 input) - HDCP com- pliant DVI-D (1 input) - HDCP compliant
RJ45 CAT6 (with loop)	Addressable RS422 monitor control by AHnet protocol
GPI (SubD9)	Up/Down control
USB	For service

Control	
RJ45, RS-422 (I/O), AHN	et protocol
Addressing	
Termination switch	
GPI	
IR Remote control (monito	or adjustments): 1/5
Movement's Control	
User interface on monitor	(Up/Down) Capacitive touch sensor
Remote	RS-422 I/O, GPI
Electrical	
External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	50W
Accessories	
ERT	Ethernet Interface Unit
ERT Mechanical	Ethernet Interface Unit
	Ethernet Interface Unit
Mechanical	Ethernet Interface Unit 424 x 241 x 20mm [16.69" x 9.49" x 0.79"]
Mechanical Monitor Dimensions:	424 x 241 x 20mm
Mechanical Monitor Dimensions: Screen	424 x 241 x 20mm [16.69" x 9.49" x 0.79"] 424 x 80 mm
Mechanical Monitor Dimensions: Screen Top frame	424 x 241 x 20mm [16.69" x 9.49" x 0.79"] 424 x 80 mm [16.69" x 0.79"] 525 x 607 x 80 mm
Mechanical Monitor Dimensions: Screen Top frame Housing below the table	424 x 241 x 20mm [16.69" x 9.49" x 0.79"] 424 x 80 mm [16.69" x 0.79"] 525 x 607 x 80 mm [20.6" x 23.9" x 3.15"]
Mechanical Monitor Dimensions: Screen Top frame Housing below the table Weight	424 x 241 x 20mm [16.69" x 9.49" x 0.79"] 424 x 80 mm [16.69" x 0.79"] 525 x 607 x 80 mm [20.6" x 23.9" x 3.15"]

OPTIONS

- Projected capacitive multi-touch screen
- Black anodised
- Gold finish
- Bronze finish
- Painted
- Aluminium cover plate
- DynamicLoop


WARRANTY

- 5 years limited warranty
- 2 years general warranty


CERTIFICATIONS

- CE
- FCC
- IECEE

CONNECTIVITY PANEL AH 17DB2



INTERACTIVE SETUP DISPLAY (ISD)



CONSULTANTS, ARCHITECTS AND ENGINEERS SPECIFICATIONS

Vertically retractable motorised 17.3" Full HD professional monitor. The monitor housing shall be made of milled anodised aluminium with a maximum thickness of 20 mm and the screen shall be protected with an anti-reflecting 2 side coating black edged 2 mm glass. The monitor shall allow its installation into furniture opening with a maximum width of 24 mm and shall be designed to be veneered to match the furniture's surface.

The monitor housing shall be flush with the table when the monitor is in recessed position. A capacitive button that shall be placed at the top of the monitor shall activate the monitor's movements. The monitor shall have a brightness of 400 cd/m2, a contrast ratio of 600:1 and a backlight lifespan of 50,000 hours.

The monitor shall provide 2 DVI HDCP inputs by a licensed HDCP monitor manufacturer. The monitor shall provide an addressable RS-422 and an easy to read Interactive Setup Display (ISD) to access the safety parameters, the setup of the speed and the control of the brightness, contrast and backlight. The monitor shall be able to run an auto adjustment program to reset the factory setups.

The monitor shall provide a USB port for firmware upgrades. The monitor shall be controlled by a wireless Android and iOS App providing information about the monitor's serial number, and providing access to the control and to the setup menu.

General Dimensions AH 17 DB 2

