

## AH1

HDCP compliant aluminium manually foldable monitor



### FEATURES

- Milled anodised aluminium monitor
- Manually foldable from 0 to 70°
- Totally adjustable position
- No need to modify the desk surface
- USB pass-through
- Maintenance free
- Energy saving design, low consumption video controller

### GENERAL

Arthur Holm AH1 are aluminium manually foldable monitors for table top with a natural anodised finish and a black cast iron base. The multifunctional iron base serves for several purposes: the unobstructed base holds firmly the aluminium monitor housing in place and provides a steepless adjustment of the viewing area. Furthermore, the base hides the cable connection and guides the cables unseen away from the monitor when using the cable exit in the centre of the base or, if needed, the rear cable outlet.

The screen position can be easily adjusted from flat on the table to 70° . The monitors include a USB passthrough from the side. AH1 are the ideal solution for auditoriums, telepresence, training rooms, meeting and conference rooms and information counters.

---

#### ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com  
Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

Technology serving Design

**Display**

Size	Full HD 21.5" TFT Active Matrix, widescreen
Resolution	1920 (h) x 1080 (v)
Brightness	350 cd/m2
Contrast ratio	1000:1
Pixel	0.24975 (h) x 0.24975 (v) mm
Viewing angle	89°/89° (L/R)/89°/89°(U/D)
Viewing area	476.064 (h) x 267.786 (v)
LED backlight lifespan	50,000 hrs
Response time	Tr 12ms, Tf 10 ms
Temperature (operating/storage)	Operating 0°C ~+40°C Storage -20°C ~+60°C

**Materials**

Monitor housing	Milled aluminium with anodised finishing and dark grey cast iron base
Glass	Flush antiglare protection glass with elegant black marking

**Connectivity**

Input signal	DVI-I (1 input) – HDCP Compliant DVI-D (1 input) – HDCP Compliant
--------------	--

**Electrical**

External power supply	100-240 Vac, 47/63Hz, 12Vdc
Power consumption	60W

**Mechanical**

Monitor Dimensions:	
Monitor Dimensions	538.8 x 381.6 x 57 mm [21.21" x 15.02" x 2.24"]
Weight	20 Kg / 44.09 Lbs
Shipping Dimensions:	
Weight	21.1 Kg / 46.8 Lbs
Shipping Box	700 x 560 x 225 mm [27.55" x 22.04" x 8.85"]


**OPTIONS**

- Laser engraved logo
- Projected capacitive multi-touch screen
- Black anodised
- Gold finish
- Bronze finish

**CERTIFICATIONS**

- CE
- FCC
- IECEE

**CONNECTIVITY PANEL**



**CONNECTIVITY**

- 1- DVI-1 /DVI-A video input - analog /digital
- 2- DVI-2 video input - digital
- 3- 12 D.C. power supply input

**CONSULTANTS, ARCHITECTS AND ENGINEERS SPECIFICATIONS**


The monitor shall provide a manually adjustable position from 0 to 70°. The monitor housing shall be made of anodised aluminium with a double sided anti-reflective 3 mm front glass with black marking. The monitor shall provide a black cast iron base with hidden cables and no visible screws.

The 21.5" Full HD monitor shall have a brightness of 350 cd/m2, a contrast ratio of 1000:1 and a backlight lifespan of 50,000 hours.

The monitor shall provide 2 DVI HDCP inputs by a licensed HDCP manufacturer and a USB pass-through.

**WARRANTY**

- 2 years general warranty



ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com  
 Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

Technology serving Design