AH22D3R16GA



Dynamic3

HDCP compliant aluminum foldable and rotatable monitor







≺ AHlink Arthr	ur Holm	
Dynamic3 (577FW203)		
Serial: 00000	Serial: 000000000	
Ver: 1.18		
Control		
MOV OPEN	I CLOSE CLOSE	
DISP O	N OFF	
DVIA DVI1 DVI2		
BACKL		
	50	
BRIGH 50		
SAVE VALUES AHLink OFF		
Command: 00:00:00:00:00		
S1 S2	S3 S4	
AHnet Address 1		
Position 8		
PASSWORD: 0		



Highlights

- Entirely built of aluminum
- Opens, folds down and rotates 180°
- 2 working positions (vertical and horizontal)
- Adjustable and memorisable tilt angle from 90 to 110°
- Automatic image flip
- Synchronized tray lift movement
- Floating security sensor
- Energy saving design, low consumption video controller
- 2 DVI I/HDCP compliant
- RS422/RS4851/0
- ISD: Interactive Setup Display for adjustments and service
- AHlink: Wireless connectivity for setup, adjustments and service
- AH-AMMC: Auto Mechanical Movement Calibration

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

AH22D3R16GA

General

Arthur Holm Dynamic3 is a motorized product range that provides different working positions while keeping a low profile inside the working desk and a perfect integration in the furniture. The aluminum monitor housing rises and leans, has an additional 180° rotation movement, and retracts inside the work surface in 2 different positions: with the monitor oriented up or down.

The screen's lifting system automatically activates the elevation of a tray where keyboard and mouse can be placed. We have selected the best possible aluminum finishing specifications in the world, providing the maximum technical and visual performance and the screen is protected with an anti-reflective 2 side coating 3 mm black edged glass.

Dynamic3 is available from 15.6" to 21.5", with 2 DVI-HDCP compliant inputs and equipped with an interactive setup display (ISD) allowing the control, setup and diagnose of the monitors. Monitors provide RS-422 I/O allowing the remote control of movements, speeds, safety settings, brightness, contrast and backlight.

The monitor can also be adjusted and controlled via a wireless application: AHlink. The AHlink Android and iOS App allows the access to the setup and control menu and to get the serial number and firmware version without removing the monitor from the table. The Auto Mechanical Movement Calibration automatically adjust the speeds and the safety protection parameters. The use of the ERT-30 and ERT-60 enables an automatic individual address configuration of all the monitors in a meeting table.

Technical Specifications

Display

Display	
Size	FULL HD 21.5" TFT Active Matrix
Resolution	1920 (h) x 1080 (v)
Brightness	350 cd/m2
Contrast ratio	1000:1
Pixel	0.24975 (h) x 0.24975 (v) mm
Viewing angle	89°/89° (u/d) / 89°/89° (l/r)
Viewing area	408.96 (h) x 230.04 (v) mm
LED backlight lifespan	50,000 hrs
Response time	Tr 37ms, Tf 3 ms
Temperature	Operating 0°C - +40°C
(operating/storage)	Storage -20°C - +60°C
Materials	
Monitor housing	Anodized Aluminum
Glass	AR 2 side with an anti-reflective
	coating on the glass surface.
	Thickness: 3.0 ± 0.3 mm
Cover plate	Anonized aluminum
Connectivity	
Input signal	DVI-I (1 input) - HDCP Compliant
	DVI-D (1 input) - HDCP Compliant
RJ45 CAT5 (with loop)	Addressable RS422 monitor
	control by AHnet protocol
GPI (SubD9)	Movements Control
0.1 (00.007)	

Control

Control	
RJ45, RS-422 (I/O)	
Addressing	
Termination switch	
GPI	
IR Remote control (monito	or adjustments): 1/5
Movement's Control	
User interface on monitor	(Up/Down/Face Up))
Remote	RS-422 I/O/GPI
Electrical	
Low voltage (external power supply)	100-240Vac, 47/63Hz, 12Vdc
Power consumption	55W
Mechanical	
Dimensions:	
Upper cover plate	609 x 477 x 4.1 mm [23.97" x 18.77" x 0.16"]
Housing below the table	595 x 456 x 102.5 mm [23.42" x 17.95" x 4.03"]
Weight	20 Kg / 44 Lbs
Shipping Dimensions:	
Weight	21 Kg / 46.2 Lbs
Shipping Box	649 x 512 x 212 mm [25.5" x 20.15" x 8.3"]

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.



Options

- Projected capacitive multi-touch screen
- Built-in DynamicTalk
- Integrated USB camera
- Integrated connectors on cover plate
- Retractable HDMI cable
- Keyboard and mouse
- DynamicLoop
- DynamicShare

Finishes


- Laser engraved logo
- Underneath installation
- Black anodized
- Gold
- Bronze
- Painted

Certifications

- CE
- FCC
- IECEE
- CB

Warranty

• 2 years general warranty







ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

Connectivity Pannel



Interactive Setup Display




Consultants, architects and engineers specifications

Motorized foldable and rotatable 21.5" Full HD professional monitor. The monitor housing shall be made of milled anodized aluminum and the screen shall be protected with anti-reflective 2 side coating black edged 3 mm glass. The monitor shall have a brightness of 350 cd/m2, a contrast ratio of 1000:1 and a backlight lifespan of 50,000 hours.

The monitor's opening mechanism shall activate automatically the rising of a synchronized aluminum tray covering the entire opening surface. The monitor shall provide 2 working positions: vertical with an adjustable tilt angle of up 20° and horizontal flush on the table. The monitor shall be capable to rotate 180° and be folded with the screen facing down. The monitor shall provide an automated image adaptation for vertical and horizontal monitor position. The monitor shall provide 2 DVI HDCP inputs by a licensed HDCP monitor manufacturer. The monitor shall provide an addressable RS-422/RS-485 and an easy to read Interactive Setup Display (ISD) to access the safety parameters, the setup of the speeds and the control of the brightness, contrast and backlight. The monitor shall be able to run an autoadjustment program to reset the factory setups. The monitor shall provide a USB port for firmware upgrades. The monitor shall be controlled by a wireless Android and iOS app providing information about the monitor's serial number, and providing access to the control and to the setup menu.

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.



ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 Sant Hipòlit de Voltregà 08512 Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

Technology serving Design