

D3

Professional compact foldable monitor







Highlights

- Motorized aluminum foldable monitor
- Anti-reflective 2 mm black-edged glass
- Compact design with 83.5 mm [3.29”] depth from the table surface
- Adjustable viewing angle from 90° to 110°
- Control via capacitive touch sensor on the cover plate or via remote control
- Unique mechanism with a patented synchronized tray movement
- Silent mechanical movement
- 2/DVI HDCP-compliant inputs
- Optional control interface sensor buttons on glass: Video source selection and Share
- Interactive Setup Display
- AH-AMMC: Auto Mechanical Movement Calibration

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.
MakeYourMeetingsCount

General

D3 is a compact, motorized folding monitor designed to maximize usable space above and below the table. Its shallow installation depth minimizes the space required beneath the tabletop, preserving comfortable legroom. Ideal for open table design in control rooms, meeting rooms, boardrooms, and reception areas, D3 folds flat into the table when not in use.

Crafted from premium natural anodized aluminum, D3 features a synchronized tray that rises together with the display to optimize the working surface. The tray can be configured to accommodate a keyboard and mouse. The monitor offers two HDCP-compliant DVI inputs and can be operated using a capacitive touch sensor, remotely via RS-422/485, or through the AHlink app via ERT.

The screen is protected by 2 mm anti-reflective glass. Optional controls can be integrated on the glass for input selection, sharing, and free buttons.

The rear panel can be veneered in the UI version to blend seamlessly with the tabletop. D3 also includes anti-pinch safety protection, an interactive setup display, and an automatic mechanical movement calibration system.

Options include a variety of finishes, a touchscreen, cameras, and connectors integrated into the cover plate.

Technical Specifications

Display	
Size	FULL HD 17.3" TFT Active Matrix, widescreen format.
Resolution	1920 (h) x 1080 (v)
Brightness	480 cd/m2
Contrast ratio	1100:1
Pixel	0.1989 (h) x 0.1989(v) mm
Viewing angle	85°/85° (u/d) / 85°/85° (l/r)
Viewing area	381.888 (h) x 214.812 (v) mm
Response time	Tr + Tf 16 ms
Temperature *(operating/storage)*	Operating 0°C – +40°C Storage -20°C – +60°C

Materials	
Monitor housing	Anodized Aluminum
Glass	Anti-reflective coating on the glass surface. Thickness: 2.0mm ± 0.2 mm
Cover plate	Anodized aluminum

Connectivity	
Input signal	DVI-I (1 input) – HDCP Compliant DVI-D (1 input) – HDCP Compliant
RJ45 CAT5 (with loop)	Addressable RS422 monitor control by AHnet protocol
GPI (SubD9)	Movements Control (opto isolated)
USB	For service (firmware upgrades)

Control
RS45, RS-422 / RS-485 Full Duplex (I/O)
Addressing
Termination switch
GPI
IR Remote control (monitor adjustments): 1 Remote control is provided every 5 motorized devices

Movement's Control	
User interface on monitor	(Up/Down)
Remote	RS-422/RS-485 Full Duplex I/O/GPI

Electrical	
Low voltage	100-240Vac, 47/63Hz, 12Vdc
Power consumption	50W

Mechanical Dimensions:	
Screen	414 x 261 x 18 mm [16.30" x 10.28" x 0.71"]
Upper cover plate	485 x 380.50 x 4 mm [19.09" x 14.98" x 0.16"]
Housing below the table	83.50 x 367 x 472 mm [3.29" x 14.45" x 18.58"]
Weight	10 Kg / 39.02 Lbs
Shipping Dimensions:	
Weight	11Kg / 41.4 Lbs
Shipping Box	559 x 469 x 222 mm [22" x 18.46" x 8.74"]

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

Options

- Prepared for veneer
- Prepared for keyboard and mouse
- Projected capacitive multi-touch screen
- DynamicLoop
- DynamicShare
- PC Box
- Camera
- Connectors on the cover plate
- Black anodized
- Painted


Certifications

- CE
- IECEE
- CB
- EMC
- RoHS


Warranty

- 2 years general warranty

Connectivity Pannel



Interactive Setup Display



Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.
MakeYourMeetingsCount

Consultants, architects and engineers specifications


Motorized foldable 17.3" Full HD professional monitor. The monitor housing shall be made of milled anodized aluminum and the screen shall be protected with anti-reflective 2 mm glass. The monitor shall have a brightness of 480cd/m2, a contrast ratio of 1100:1.


The monitor's opening mechanism shall automatically raise a synchronized aluminum tray that covers the entire opening surface. The depth from the table surface shall be 83.5 mm [3.29"]. The monitor shall fold down with the screen facing downward.


The monitor shall provide 2 DVI HDCP inputs by a licensed HDCP monitor manufacturer. The monitor shall provide an addressable RS-422 and an easy to read interactive setup display (ISD) to access the safety parameters, the setup of the speeds and the control of the brightness, contrast and backlight and remote setup support and diagnostic. The monitor shall provide a safety system that detects obstructions causing the unit to stop. The monitor shall be able to run an auto-adjustment program to reset the factory security ratio between its factory movement speed and its protection parameters adapting the unit to the way it has been installed. The monitor shall provide a USB port for firmware upgrades.


The monitor shall be compatible with wireless connectivity for setup and control via AHlink when used in combination with an ERT.

General Dimensions









Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.