



DB3Talk

HDCP compliant aluminum retractable motorized monitor with an independent lift for gooseneck microphone



AHlink : the App for setup, control and diagnose



Highlights

- Vertical motorized monitor with an independent microphone lift
- Adjustable monitor angle from 90° to 20°
- Stepless memorizable monitor angle
- Automated hatch in black acrylic glass or for table surface matching (veneer)
- Milled black anodized aluminum housing
- Anti-reflective 2 mm black-edged glass
- Interactive Setup Display (ISD)
- HDCP compliant
- Energy saving design, low consumption video controller
- RS-422/RS-485 Full Duplex I/O
- Wireless connectivity for setup and control via AHlink when ERT installed
- Auto Mechanical Movement Calibration (AH-AMMC)

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 · 08512 Sant Hipòlit de Voltregà · Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

MakeYourMeetingsCount

General

Professional motorized monitors with a minimal impact on the table's design when retracted and an astonishing impact on the table when ejected with an adjustable monitor's position from 90° to 20°, including an independent lift system for 3 pin XLR gooseneck microphones beside the monitor within the same mechanical housing.

The design of the automated hatch allows it to be matched to the table surface by adding the same material as the tabletop on top of it (optional), providing a streamlined finish to the furniture. The automated hatch is made of black acrylic glass.

The user can adjust the screen position for comfort and visibility, with full view of the other participants around the table. The screen inclines smoothly towards the user, who can adjust the monitor's position

by simply touching a capacitive button located on the glass of the screen, stop the movement and lock the position at the desired angle. A memory function will allow to store and recall the desired position.

The screen housing is made of black anodized aluminum and is protected with an anti-reflective 2 mm black edged glass. DB3Talk are available from 17.3" to 23.8" with 2 HDCP compliant DVI or HDMI inputs and equipped with an Interactive Setup Display (ISD) allowing the control, setup and diagnose of the monitors.

The microphone lift shall have 3 operation buttons; open/close, mute/unmute the microphone and GPO button. And both the monitor and the microphone's lift shall operate with only one external power supply.

Technical Specifications

Display

Size	4K 23.8" TFT Active Matrix, widescreen format. LED backlight
Resolution	3840 (h) x 2160 (v)
Brightness	250 cd/m2
Contrast ratio	1300:1
Pixel	0.13695 (h) x 0.13695 (v) mm
Viewing angle	89° / 89° (l/r) 89° / 89° (u/d)
Viewing area	525.888 (h) x 295.812 (v) mm
Response time	Tr + Tf 14ms
Temperature (operating/storage)	Operating 0°C ~ +40°C Storage -20°C ~ +60°C

Materials

Monitor housing	Solid mechanized aluminum housing with black anodized finish. Front black-edged glass.
Hatch	Black acrylic glass
Base plate	Black acrylic glass

Connectivity

Input signal	2 x HDMI - HDCP compliant
RJ45 CAT6 (I/O)	Addressable RS-422/RS-485 control by AHnet protocol
GPI (SubD9)	Up/Down control (opto isolated)
USB	For service (firmware upgrades)

Electrical

External power supply	100-240Vac, 50/60Hz, 12Vdc
Power consumption	80W

Control

DynamicTalk Control
RJ45, RS-422/RS-485 Full Duplex (I/O), AHnet protocol
AHlink
Addressing
Termination switch
GPI
Microphone control button on glass
Customized function buttons on glass
Remote control (monitor adjustments): 1 Remote control is provided every 5 motorized devices

Movement's Control

User interface on monitor	(Up/Down) Capacitive Touch Sensor
Remote	RS-422 / RS-485 Full Duplex (RJ45 CAT 6)

Accessories

ERT-30 / ERT-60	Ethernet Interface Unit
-----------------	-------------------------

Mechanical Dimensions

Screen	565 x 40 x 371.67mm [22.24" x 1.57" x 14.63"]
Top frame	673 x 47mm [26.5" x 1.85"]
Housing below the table	741 x 145.50 x 630mm [29.17" x 5.73" x 24.80"]
Weight	30Kg / 66.14lb aprox.

Packaging Dimensions

Box	870x255x715mm [34.25" x 10.04" x 28.15"]
Weight	31Kg / 68.34lbs aprox.

ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 · 08512 Sant Hipòlit de Voltregà · Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com
Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

MakeYourMeetingsCount

Options and accessories

- Projected capacitive multi-touch screen
- Integrated USB camera
- Retractable USB-C cable
- Automated hatch ready for veneering with capacitive sensor
- ERT-30/ERT-60

Warranty

- 2 years general warranty

Consultants, architects and engineers specifications

Vertically motorized 23.8" 4K professional monitor with an inclination from 90 to 20 degrees on the table surface including a universal microphone lift system.

The monitor housing shall be made of milled anodized aluminum with a 20 mm. thickness and the screen shall be protected with an anti-reflecting 2 mm glass.

The automated hatch shall slide down inside the mechanism and shall close the table cut off flush on the table.

A capacitive button shall be placed on the automated hatch to activate the monitor's movement. The movements of the monitor shall be controlled by 3 buttons located on the monitor's front glass; the user shall memorize the monitor's position, by pressing both movement control buttons simultaneously. Optionally, an Input Source Selection shall be located on the monitor's front glass to switch between the different signal inputs. The monitor shall have a brightness of 250cd/m², and a contrast ratio of 1300:1

The system shall include an independent lift system for 3 pin XLR gooseneck microphones beside the monitor within the same mechanical housing. Both the monitor and the microphone's lift shall operate with only one external power supply. The microphone lift must have 3 operation buttons; open/close, mute/unmute the microphone and free GPO button.

Certifications

- CE
- IECEE
- CB
- RoHS

The lift system shall include an automated turning system of the microphone and a plastic rounded ring to centre the microphone during its rise and retract movement from a position hidden to a top position projected through the guide, preventing the microphone from scratching the monitor housing and surrounding parts, damaging or blocking when retracting.


The system shall be equipped with RS-422/RS-485 Full Duplex, RJ-45 and AHnet open protocol allowing individual remote control, setup and diagnostic of up to 30 units per line. GPI (contact close to control movements), GPO (contact close to detect button activation) and a USB for firmware updates.

The unit shall provide a safety system that detects obstructions and causes the unit to stop with an audio indication. The unit shall provide and auto-calibration mode to reset mechanical speeds and safety adjustments. The system shall provide an automatic RS-422/RS-485 Full Duplex addressing system when used in combination with ERT-30 and ERT-60.


The unit shall be compatible with a wireless app that allows the exact adjustment of the microphone length, facilitates the unit's serial number, allows the activation and de-activation of the RS-422 termination and allows to change the working mode from PA to Conference.

The monitor shall provide 2 HDMI HDCP inputs by licensed HDCP manufacturer. The monitor shall be compatible with the AHlink wireless Android and iOS App for the setup, diagnosis and control.

Connectivity Panel




Interactive Setup Display (ISD)





General Dimensions



AH24DB3Talk 4K



↑
D



VIEW D



ARTHUR HOLM

Albiral Display Solutions SL · Fàtima, 25 · 08512 Sant Hipòlit de Voltregà · Barcelona, Spain · +34 938 502 376 · marketing@arthurholm.com · www.arthurholm.com

Arthur Holm is a registered brand of Albiral Display Solutions SL. Specifications subject to change without previous notice.

MakeYourMeetingsCount